

# Specifications at a Glance\*

## Printer Name

GC420™

## Standard Features

- 32 bit RISC processor
- Programming languages: EZPL (ZPL, ZPL II and EPL2)
- Triple connectivity: USB, parallel and serial
- Print methods: Direct thermal and thermal transfer, printing of barcodes, text and graphics.
- OpenACCESS™ for easy media and ribbon loading
- Microsoft® Windows® drivers

## Printer Specifications

### Resolution

203 dpi/8 dots per mm

### Memory

8 MB Flash, 8 MB SDRAM (standard)

### Print Width

4.09"/104 mm

### Print Length

39"/990 mm

### Print Speed

4"/102 mm per second maximum

### Media Sensors

Reflective and transmissive sensors

## Media Characteristics

### Media width

1.00"/25.4 mm to 4.25"/108 mm

### Media length

0.38"/9.6 mm to 39"/990 mm

### Maximum media roll size

5"/127 mm O.D. on a 1.00"/25.4 mm, 1.5"/38 mm I.D. core

### Media thickness

0.003"/0.08 mm to 0.007"/0.18 mm

### Media types

- Roll-fed or fan fold
- Label stock (die cut or continuous, direct thermal or thermal transfer)
- Tag stock (die cut or continuous, direct thermal or thermal transfer)
- Receipt paper (continuous, direct thermal)
- Wristband stock (direct thermal or thermal transfer)

## Ribbon Characteristics

### Outside diameter

1.34"/34 mm

### Standard length

244' (74 m)

### Ribbon capacity

1:1 One ribbon per roll of media

### Width

1.33"/33.8 mm to 4.3"/110 mm

### Core I.D.

0.5"/12.7 mm

## Operating Characteristics

### Environmental

- Operating Temp: 40° F/5° C to 105° F/41° C
- Storage Temp: -40° F/-40° C to 140° F/60° C
- Operating Humidity: 10% to 90% non-condensing R.H.
- Storage Humidity: 5% to 95% non-condensing R.H.

## Agency Approvals

TUV-R NRTL, TUV-R CB, NOM, KCC, CE, FCC Class-B

## Physical Characteristics

	GC420d	GC420t
• Width:	7.9"/201 mm	7.9"/201 mm
• Height:	6.7"/170 mm	6.8"/173 mm
• Depth:	8.2"/208 mm	9.4"/239 mm
• Weight:	3 lbs/1.4 kg	3.2 lbs/1.5 kg

## Zebralink™ Solutions

### Software

- ZebraDesigner™ Pro—An intuitive, easy-to-use software program for creating complex label designs (option)
- ZebraDesigner—Offers basic features for simple label design
- ZebraDesigner Driver—The most powerful driver available from Zebra

### Firmware

- ZPL II\*—Zebra Programming Language provides sophisticated label formatting and printer control.
- EPL2™—Eltron Programming Language with Line Mode simplifies label formatting and enables format compatibility with legacy applications.

## Communication and Interface Capabilities

- Centronics® parallel (36 pin) connector ports
- RS-232 Serial interface
- USB V1.1 interface, bi-directional

## Fonts/Graphics/Symbologies

- 16 resident expandable ZPL fonts
- One resident scalable ZPL font
- 5 resident expandable EPL2 fonts
- Supports user-defined fonts and graphics—including custom logos

## Bar Code Symbologies

- Bar Code Ratios: 2:1 (non-rotated) and 3:1
- Linear Bar Codes: Code 11, Code 39, Code 93, Code 128A, B & C (User selectable/Auto), UCC/EAN-128, Code 128, UPC-A, UPC-E, EAN-8, EAN-13, EAN-14, UPC-A and UPC-E with EAN 2 or 5 digit extensions, UPC-E with 2 and 5 add on, Plessey, POSTNET, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar, and GS1 DataBar™ (formerly RSS), Postnet (5, 9, 11 & 13 digit) Japanese Postnet, Plessey (MSI-1), MSI-3, German Post Code, RSS-14 (limited, truncated, stacked).
- 2-Dimensional: PDF417 (MicroPDF-417 and MacroPDF-417), Code 49, Maxicode, Codablock, Data Matrix, QR code, and Aztec.

## Options and Accessories

- Dispenser—Label peel and present with label present sensor
- KDU and KDU Plus™—Keyboard display units for stand-alone printing applications

## Electrical Specifications

- Auto-ranging external power supply with C7 type connector
- Output: 20 VDC, 2.5A
- Input: 100-240 VAC, 50-60 Hz

\*Specifications subject to change without notice.  
©2012 ZIH Corp. All rights reserved. All product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic, ZPL, ZPL II and ZebraNet are registered trademarks of ZIH Corp. All rights reserved. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Centronics is a registered trademark of Centronics Data Computer Corporation. All other trademarks are the property of their respective owners.