

# Specifications - CTS2000 Series

---

<b>Printing Method</b>	Line Thermal Dot Printing 82.5mm Paper: 80mm/640 Dots
<b>Printing Width</b>	80mm Paper: 72mm/576 Dots 60mm Paper: 54.5mm/436 Dots 58mm Paper: 54mm/432 Dots
<b>Printing Speed (Max.)</b>	approx. 220 mm/Sec (52 lines/sec)
<b>Number of Columns</b>	Font A - Max. 53 Columns Font B - Max. 71 Columns Font C - Max. 80 Columns
<b>Character Size</b>	Font A: 1.25 x 3.00mm (12 x 24 dots) Font B: 0.88 x 3.00mm (9 x 24 dots) Font C: 0.88 x 2.00mm (8 x 16 dots) Alphanumeric Character (Font A, B & C)
<b>Character Table</b>	Code Page 437, 850, 852, 857, 860, 863, 864, 865, 866, Katakana, WPC1252, Thai code 18
<b>Line Spacing</b>	4.23mm (1/6 inch, can be set by a command)
<b>Paper feed method</b>	Friction
<b>Paper Type</b>	Thermal Paper Roll
<b>Paper Width</b>	82.5 ± 0.5mm, 80 ± 0.5mm, 60 ± 0.5mm or 58 ± 0.5mm
<b>Paper Roll Diameter</b>	Max Ø 102.0mm
<b>Paper Supply Method</b>	Easy Paper Loading, Drop in and Print
<b>Emulation</b>	ESC/POS
<b>Print Buffer</b>	4K bytes / 45 bytes
<b>NV Memory</b>	Max 384 Kbytes
<b>Sensors</b>	Paper Near End Sensor, Paper End Sensor , Rear Cover Open Sensor
<b>Drawer Ports</b>	2 ports
<b>Auto cutter</b>	Sliding Cutter, partial cut possible
<b>Standard Interfaces Available</b>	USB & Parallel (IEEE1284 Compliant) USB & Serial (RS232C)
<b>Driver available</b>	Windows 2000/NT/XP/2003 server, OPOS
<b>Weight</b>	2.0 Kg
<b>External Dimensions (W x D x H)</b>	147 x 207 x 147 mm
<b>Power Supply (Adapter)</b>	Input: AC100 ~240V, 50/60Hz, 150VA Output: DC 24V,2A

